

Material Safety Data Sheet H431

Further Physical Properties and Descriptive Literature is Available on Request or On Our Web Site

Section 1 - Product Information

Product Name: H431

Description: Clay/Mineral blend used for Pottery (moist pugged)

Product Use: Pottery

CEPA Status: All ingredients listed on Canadian domestic substances list (DSL)

WHMIS Class:

EPA TSCA Status: No hazardous classes apply

All ingredients are included in the inventory

*Respirable Free Hazardous Ingredient Silica (Quartz) % 14808-60-7 CAS Number OSHA PEL 3 mg/m² 0.01 mg/m3 ACGIH TLV

*Note: Free Silica is not a hazard in moist or wet form, it is only a hazard if clay is dry and dust is generated.

Physical State: Odour and Appearance: "pugged" refers to the wet plastic material Light grey powder, grey pugged Solid Density, Evaporation Rate, Boiling Point, Freezing Point, pH, Specific Gravity, Coeff. Water/Oil Dis. Odour Threshold, Vapour Pressure & Physical Properties Not Applicable:

Consider dust as

Non-Flammable and Non-Explosive

Flammability: ⊠ Yes ☐ No

Flammable Limit, Hazardous Combustion Products, Sensitivity to Impact, Sensitivity Temperature, Upper Flammable Limit, Lower Flashpoint and Method, Autoignition Non-Applicable Data: Means of Extinction,

Kiln Burning: Carbon Monoxide, Products of Decomposition During

Carbon Dioxide and possible traces of Sulfur Dioxide. Vent kiln during firing.

Section 5 - Reactivity Dat

Static Discharge

eq:chemical Stability: \$\$ \$\$ Yes \$\$ \$\$ O conditions of Instable Incompatibility with Other Substances \$\$ Yes \$\$ No In \$\$	Instability: None Solubility in Water: No Incompatible Substances: None	Water: No

nazardous Decomposition Products: See section 4

Reactivity, and Under What Conditions: Inert and Non-Reactive

Product Identifier: H431

Route of Entry:	
Skin Contact	e e e e e
Skin Contact Skin Absorption Skin Contact Numbership	out of toxicolic
Fve Contact	Sient Liebie
⊠ Inhalation	i dien
Innection	

Effect of Acute Exposure to Product A nuisance dust, heavy exposure may cause mechanical irritation of the respiratory tract.

Irritancy of Product: Mechanical Irritant Only

Non-Applicable Properties: Sensitization, Teratogenicity, Reproductive Toxicity,

Effects of Chronic Exposure to Respirable Quartz Dust: IARC has found evidence inhalation of dust. Long term exposure may cause silicosis. for the carcinogenicity of crystalline quartz. Avoid prolonged or repeated

Exposure Limits to Quartz: TLV = 0.1 mg/m respirable crystalline silica

Synergistic Products: Tobacco smoke will increase lung damage

Footwear: Not applicable unless wet material is a Gloves: Not Req'd Personal Protective Equipment Special Clothing: Not Req'd Approved Respirator Respirator (Specify): where TLV exceeded contact lenses are worn direct contact or where in high dust conditions mechanical irritation Eye: May cause

to less than permissible exposure limits is recommended Ventilation: Local exhaust or other ventilation that will reduce dust concentration

Leak and Spill Procedure: Aqueous slurry is a slipping hazard. excessive dust generation, if sweeping use dust suppressant If pry minimize

Skin Contact Wash with water.

Waste Disposal at Landfill: Treat this as a blend of naturally occurring minerals.

Storage Requirements: No special requirements, store powders in dry area.

Special Shipping Information: Not required.

receive training in safe work habits, respiratory protection and health risks. Education: Many governments require that personnel working with crystalline silica

Clothing: Do not wear clothing dusted with this product in your home.

Section 8 - First Aid Mea

Skin - Wash with water

Eyes - Flush with running water until material is removed

Phone Number

Plainsman Clays Limited

Prepared by

(403) 527-8535

Date: Jan 1, 2015